



IMPACTPRO® SATIN

Cleaning & Maintenance Guide

Routine care for smooth satin hygienic wall cladding

DOCUMENT	IMP-SA-CM-001
REVISION	Rev A
ISSUE DATE	10 August 2026

CLEANING PROCEDURE

Initial clean after installation

- Allow adhesive and sealant to cure before cleaning.
- Remove protective film only when installation work is complete.
- Remove installation dust and light contamination with a soft non-abrasive cloth.

Routine cleaning

- Use a soft cloth with mild soap or detergent.
- Cleaning water or solution should not exceed 60°C.
- Increase cleaning frequency to suit traffic, contamination risk and site hygiene procedures.

Stubborn contamination

- Use a compatible alkaline cleaner with a soft cloth.
- Do not use abrasive pads, wire wool or aggressive mechanical scouring.
- Avoid unverified solvents or abrasive products that may alter the satin appearance.
- Where hot-water pressure cleaning is approved, maintain at least 600mm between nozzle and sheet surface.

DO	DO NOT
Use soft non-abrasive cloths and compatible detergents.	Use abrasive pads, wire wool or aggressive scouring.
Clean spills promptly.	Allow staining contamination to remain on the surface.
Follow site-specific hygiene procedures.	Direct high-pressure cleaning close to joints, profiles or edges.
Use clean water for final rinsing where appropriate.	Use cleaners above 60°C without technical confirmation.