



IMPACTPRO® CALYX

Cleaning & Maintenance Guide

Routine care for the printed, precision-engraved and hard-coated tile-effect surface

DOCUMENT	IMP-CX-CM-001
REVISION	Rev A
ISSUE DATE	10 August 2026

CLEANING PROCEDURE

Initial clean after installation

- Allow adhesive and sealant to cure before cleaning.
- Remove protective film and loose installation debris carefully.
- Use a soft clean cloth or non-abrasive pad with a compatible neutral detergent.

Routine cleaning

- Clean the entire decorated face, including engraved grout-effect lines.
- Use suitably diluted compatible neutral detergent and clean water as required.
- Do not exceed 60°C cleaning temperature.
- Increase cleaning frequency to suit use, traffic and local hygiene procedures.

Products and methods to avoid

- Abrasive pads or powders.
- Wire wool and sharp scrapers.
- Unapproved solvents or aggressive chemicals.
- Tools or methods that may scratch, polish or damage the matt hard-coated surface.

DO	DO NOT
Use soft, non-abrasive cleaning materials.	Use wire wool, scouring pads or abrasive powders.
Clean spills promptly.	Allow staining contamination to remain on the surface.
Clean engraved lines as part of the whole surface.	Scrape inside engraved detailing with sharp tools.
Keep cleaning temperatures within the 60°C service limit.	Apply direct steam or heat above the documented limit.